





OVERVIEW

This panel is manufactured at our TCM plant.

Applications: Residential, Light Commercial

Gauge: 24 gauge, 26 gauge and .032 Aluminum 1.5" only available in 24 gauge

Minimum Slope: 1/4 / 12 - Tube sealant recommended on pitches below 2 / 1

Minimum Slope shall comply with Florida Building Code, including Sections 1507.4.2, greater than .25/12 with recommending sealant under 2/122

Panel Profile: 16" and 15" net coverage

Substrate: Galvalume® steel sheet, conforming to ASTM A792 and and .032 Aluminum

Finish: Mill Finish AZ55 Acrylic Coated Galvalume®; 25 year limited warranty

TCM exclusive paint systems:


Core Defender Paint System® 40 / 30 year limited warranty. Max Defender Paint System® 35 / 30 year limited warranty.

COLORS

Contact your salesperson for availability information.







STRIATED

RIBBED

BENEFITS

- Superior Enery Star service colors with stability proven through extensive Valspar® testing.
- Galvalume® Mill finish or painted with TCM exclusive paint system are proven to have long life and low life cycle cost.
- Hidden fastener system for long life and low maintenance.
- FL Building Code approved to withstand harsh wind conditions. Some of our product approvals include HVHZ (High Velocity Hurricane Zone) approval. See product approval numbers below.

FLORIDA PRODUCT APPROVALS: A current list Florida Product Approvals available on our website.

For the most up-to-date Florida Product Approvals, please visit our

website: TriCountyMetals.com/florida-product-approvals/

For other installation configurations, please inquire with your salesperson for site-specific accommodations.



